



SORAA 7.5W LED MR16 3000K VIVID3 10° DIM

Item #777057

Ordering Code SM16-07-10D-930-03

UPC 849565009239

- Works with trailing edge and leading edge phase cut dimmers
- Enclosed fixture compatibility allows operation in damp or outdoor locations
- White point accuracy within 3 SDCM
- CUL rated for 12VAC NEC Class 1 and Class 2 systems
- SORAA SNAP SYSTEM compatible with spot models
- VIVID lamps offer excellent color rendering: CRI = 95 & R9 = 95
- 7.5W LED = 50W HALOGEN



TECHNICAL SPECIFICATIONS

Item #	Watts	Bulb Type	Base	Volts	Finish/Description	Beam Angle (°)	Color Temperature (CCT)
777057	7.5	MR16	GU5.3	12	N/A	10	3000K
Color	CRI	Lumens	CBCP	Average Hours	M.O.L. (inches)	M.O.D. (inches)	Incandescent Equivalent
Soft White Light	95	410	6000	35000	1.875	2.000	50W
Energy Star	DLC	Title 24 Compliant	Safety Rated	Safety Rating	Type Enclosed Rated	Dimmable	Warranty
N	N	N	UL	DAMP	Y	Y	3

Order Multiple
QTY
10

APPLICATION SUGGESTIONS



Landscape



Recessed



Track