



SORAA 7.5W LED MR16 3000K VIVID3 25° DIM

Item #777058

Ordering Code SM16-07-25D-930-03

UPC 849565009352

- Works with trailing edge and leading edge phase cut dimmers
- Enclosed fixture compatibility allows operation in damp or outdoor locations
- White point accuracy within 3 SDCM
- CUL rated for 12VAC NEC Class 1 and Class 2 systems
- SORAA SNAP SYSTEM compatible with spot models
- VIVID lamps offer excellent color rendering: CRI = 95 & R9 = 95
- 7.5W LED = 50W HALOGEN
- *Energy Star Qualified



TECHNICAL SPECIFICATIONS

| | | | | | | | |
|---------------------------|--------------|-------------------------|--------------------|----------------------------|---------------------------|--------------------------|----------------------------------|
| Item # 777058 | Watts 7.5 | Bulb Type MR16 | Base GU5.3 | Volts 12 | Finish/Description N/A | Beam Angle (°) 25 | Color Temperature (CCT) 3000K |
| Color Soft White Light | CRI 95 | Lumens 435 | CBCP 2400 | Average Hours 35000 | M.O.L. (inches) 1.875 | M.O.D. (inches) 2.000 | Incandescent Equivalent 50W |
| Energy Star N | DLC N | Title 24 Compliant N | Safety Rated UL | Safety Rating Type DAMP | Enclosed Rated Y | Dimmable Y | Warranty 3 |

Order Multiple
QTY
10

APPLICATION SUGGESTIONS



Landscape



Recessed



Track

