



SORAA 7.5W LED MR16 300K BRILLIANT 36° DIM

Item #777079

Ordering Code SM16-07-36D-830-03

UPC 849565009451

- Works with trailing edge and leading edge phase cut dimmers
- Enclosed fixture compatibility allows operation in damp or outdoor locations
- White point accuracy within 3 SDCM
- CUL rated for 12VAC NEC Class 1 and Class 2 systems
- SORAA SNAP SYSTEM compatible with spot models
- BRILLIANT lamps offer higher light output
- 7.5W LED = 65W HALOGEN



## TECHNICAL SPECIFICATIONS

|                  |       |                    |              |                    |                    |                 |                         |
|------------------|-------|--------------------|--------------|--------------------|--------------------|-----------------|-------------------------|
| Item #           | Watts | Bulb Type          | Base         | Volts              | Finish/Description | Beam Angle (°)  | Color Temperature (CCT) |
| 777079           | 7.5   | MR16               | GU5.3        | 12                 | N/A                | 36              | 3000K                   |
| Color            | CRI   | Lumens             | CBCP         | Average Hours      | M.O.L. (inches)    | M.O.D. (inches) | Incandescent Equivalent |
| Soft White Light | 85    | 525                | 1370         | 35000              | 1.875              | 2.000           | 65W                     |
| Energy Star      | DLC   | Title 24 Compliant | Safety Rated | Safety Rating Type | Enclosed Rated     | Dimmable        | Warranty                |
| N                | N     | N                  | UL           | DAMP               | Y                  | Y               | 3                       |

Order Multiple  
QTY  
10

## APPLICATION SUGGESTIONS



Landscape



Pendant /  
Downlight



Recessed



Track