



SORAA 9W LED MR16 3000K VIVID 25° 120V GU10 DIM

Item #777575

Ordering Code SM16GA-09-25D-930-03

UPC 849565024935

- Single source LED
- Narrow spot CBCPs are superior in performance at 6000Cd for 95CRI models and 7300Cd for 80CRI models
- Works with trailing edge and leading edge phase cut dimmers
- CUL rated for 12VAC NEC Class 1 and Class 2 systems
- Automatic safety shut down in any thermal environment not conducive to minimum airflow or proper ventilation
- VP3 technology for perfect and consistent rendering of colors and whites
- Enclosed fixture compatibility allows operation in damp or outdoor locations
- VIVID lamps offer excellent color rendering: CRI = 95
- 9W LED = 65W HALOGEN



TECHNICAL SPECIFICATIONS

| | | | | | | | |
|------------------|-------|--------------------|--------------|---------------|--------------------|-----------------|-------------------------|
| Item # | Watts | Bulb Type | Base | Volts | Finish/Description | Beam Angle (°) | Color Temperature (CCT) |
| 777575 | 9 | MR16 | GU10 | 120 | N/A | 25 | 3000K |
| Color | CRI | Lumens | CBCP | Average Hours | M.O.L. (inches) | M.O.D. (inches) | Incandescent Equivalent |
| Soft White Light | 95 | 490 | 2700 | 35000 | 2.200 | 1.938 | 65W |
| Energy Star | DLC | Title 24 Compliant | Safety Rated | Safety Rating | Type Enclosed | Rated Dimmable | Warranty |
| N | N | N | UL | DAMP | N | Y | 3 |

Order Multiple
QTY
10

APPLICATION SUGGESTIONS



Landscape



Recessed



Track