



SP30L BRILLIANT PAR30L / 120V 13.8W / 3000K / 9° / High Lumen*
Item #777664
Ordering Code SP30L-14-09D-830-H1
UPC 84956508811

- Single source LED
- Narrow spot CBCPs are superior in performance at 18
- Works with trailing edge and leading edge phase cut dimmers
- White point accuracy within 3 SDCM
- Automatic safety shut down in any thermal environment not conductive to minimum airflow or proper ventilation
- VP3 technology for perfect and consistent rendering of colors and whites
- SORAA SNAP SYSTEM compatible with spot models
- Enclosed fixture compatibility allows operation in damp or outdoor locations
- Ideal for recessed and track lighting
- VIVID lamps offer excellent color rendering: CRI = 95
- 18.5W LED = 100W HALOGEN



TECHNICAL SPECIFICATIONS

Item #	Watts	Bulb Type	Base	Volts	Finish/Description	Beam Angle (°)	Color Temperature (CCT)
777664	13.8	PAR30L	E26	120	Silver	9	3000K
Color	CRI	Lumens	CBCP	Average Hours	M.O.L. (inches)	M.O.D. (inches)	Incandescent Equivalent
Soft White Light	92	1230	22755	35000	4.45	3.78	120
Energy Star	DLC	Title 24 Compliant	Safety Rated	Safety Rating Type	Enclosed Rated	Dimmable	Warranty
N	N	N	UL	DAMP	Y	Y	3

Order Multiple
QTY
10